



Portable 5-Ton Air Conditioners

5T 208/1

| | | |
|---------------------------------------|---|--|
| Cooling Capacity | Btu/Hr @ 80° Drybulb and 67° Wetbulb Entering Air Temperature | 5 Ton - 63,500 |
| Heating Capacity | Btu/Hr | Optional |
| Dimensions | Width (Inches) Depth (Inches) Height (Inches) Weight (Pounds) | 34 57 43 675 |
| Electrical Characteristics | Power Supply (Volts) Power Consumption (Kilowatts) Current Consumption (Amperes) Service Required (Amperes) Min-max Voltage Power Cord Gauge Power Cord Length (Feet) | 208-230/60/1 Phase 7.7 53 60 200-240 4 110 |
| Evaporator Fan | Fan Type Air Flow (CFM) Max. External Static Pressure (Inches Of Water Gauge) Supply/Return Flanges Flange Diameter (Inches) Max. Length of Ducting (Feet) | Centrifugal 2,000 1 1/1 14 85 |
| Compressor | Compressor Type R-22 Charge (Pounds) Operating Range | Hermetic Scroll 13.0 65°F - 115°F |
| Miscellaneous Features | Remote Thermostat Compressor Overload Relay Fan Motor Protection Anti-freeze Thermostat High-Pressure Switch Compressor Short-cycle Protection Accommodates Condensate Pump Humidity Removed @60% RH (Gallons per Hour) Low Pressure Switch Phase Protection Low Ambient Operation | Optional Optional Optional Optional Yes Yes Yes 2.5 Yes N/A Optional |



Portable 5-Ton Air Conditioners

5T 208/1

Power Supply 208-230 volts 60 hertz 1 phase 53 amperes

Width 34 inches

Depth 57 inches

Height 43 inches

Weight 675 lbs

